

## Cranes



Configuration	Crane	Clamshell	Dragline
<b>OPERATING WEIGHT</b>	25,000 kg	28,000 kg	-
<b>LIFTING / BUCKET CAPACITY</b>	25,000 kg @ 3 m	-	-
<b>MAX. BOOM LENGTH</b>	31 m	22 m	22 m



Configuration	Crane	Clamshell	Dragline
<b>OPERATING WEIGHT</b>	21,775 kg	21,730 kg	21,841 kg
<b>LIFTING / BUCKET CAPACITY</b>	18,145 kg @ 3.05 m	0.76 cum	0.76 cum
<b>MAX. BOOM LENGTH</b>	27.43 m	15.24 m	15.24 m



Boom Length (m)	Jib Length(m)	Engine Power	Drive /Steer	Gross Vehicle Weight	Spec sheet
70t at 3.0m	11.5 - 44.0	9.9	200k W	4x4x4	48.3t
		17.7			
55t at 3.0m	11.1 - 42.0	9.9	200k W	4x4x4	43.0t
		17.7			
30t at 3.0m	9.7 - 31.0	7.2	160k W	4x4x4	27.0t
		12.8			
12t at 2.0m	5.3 - 23.8	3.6	125k W	4x4x4	13.365t
		5.5			



	Max. Lifting Capacity	Boom Length(m)	Engine Power	Drive/Steer	Gross Vehicle Weight
	220t at 2.5m	13.2 - 68.0	390kW	10x8x8	60t
			138kW	(10X6X8)	
	160t at 3.0m	13.2 - 60.0	390kW	10x8x8	60t
			138kW		
	110t at 3.0m	13.0 - 52.0	390kW	10x6x8	60t
			129kW	(10x8x8)	
	90t at 2.5m	11.1 - 51.2	315kW	8x6x8	48t
			128kW	(8x8x8)	
	65t at 2.5m	11.0 - 44.0	290kW	8x6x8	48t
			90kW	(8x8x8)	
	60t at 2.5m	10.4 - 40.2	240kW	6x6x6	36t
	50t at 2.5m	10.0 - 40.0	240kW	6x6x6	36t
	40t at 2.5m	10.5 - 35.2	205kW	4x4x4	24t